How to care for

your inflatable pavillion







01733 511030 sales@xldisplays.co.uk xldisplays.co.uk



MAINTENANCE



Don't use sharp objects near the Signus ONE – this can cause a puncture to the inflatable frame.

When using the Signus ONE avoid open fire or heated objects.

Avoid using chemicals when cleaning - warm water and a cloth or soft brush can be used to wipe clean the Signus ONE.

Regularly check and clean the over pressure valves—these can get clogged with dirt and this can stop them from functioning correctly.

The Signus ONE is not intended for long-term outdoor use and should be inspected for wear or damage after every event.

If the Signus ONE is losing pressure, check all valves to ensure they are secured tightly, this should prevent any further loss of air.

STORAGE



Deflate the Signus by opening the six inflation valves – Do not remove the over pressure valves.

Fold carefully and avoid kneeling on the frame or roof.

Do not pack or store the Signus wet - this can cause mould spots and discoloration. Always allow the frame and cloths to dry fully before packing away.

Signus ONE trolley box is provided for safe and easy storage – this will hold the complete inflatable pavilion when deflated and folded.

Inspect the Signus ONE fully before packing away, check for any damages that may need repair.

Use the electric pump for quicker and full deflation, the electric pump can be used to suck all the air out of the frame.

SET-UP



Unfold the inflatable frame fully before starting to inflate, straighten out any kinks in the tubes this will allow for easier and quicker inflation.

When inflating the Signus ONE, check all the valves are closed tightly, this will enable full inflation during set up.

When using outside always anchor one foot of the Signus before inflation, and the remaining two after inflation.

Inflate the three roof tubes first followed by the three leg tubes – this will create the unique Signus shape.

Always using recommended anchoring solutions when using the Signus ONE outdoors.

For outdoor use in wet weather, always add the white roof cloths, these add the water-resistant layer needed for wet weather.

Do not exceed the specified maximum air pressure when setting up the Signus ONE – 3 PSI 0.2 Bar.